

Hydraulic Hand Pumps (Aluminium - Two Stage) **NEW!**

Working Pressure 700 - 1600 - 2800 bar

Features

- Construction aluminium
- Ground and plated plungers
- Built-in factory set safety relief valve
- Durable polyurethane plunger seal
- Single Stage Pumps (Single plunger) for smaller capacity jacks
- Two Stage Pumps (Two plungers) fast approach to load
- Compatible to all reputed brand jacks
- Available in 350 and 1000 bar



OHPA-3P4-2-2

Suitable for smaller jacks



OHPA-3P4-2-4

Suitable for Std. Jacks up to 100t



OHPA-3P4-2-4-E

Suitable for Double Acting Std. Jacks



OHPA Series - O Orione H Hand P Pump A Aluminium

E - Add suffix for Direction Valve

700 bar

Pump Stage	Model	Pressure (kg/Cm ²)		Flow / stroke (cc)		Filling Capacity (ltrs.)	Usable Oil (ltrs.)	Handle Effort (kg)	Dry Weight (kg)
		1 st stage	2 nd stage	1 st stage	2 nd stage				
Two	OHPA-3P4-2-1.5	30	700	15	2.8	1.5	1	40	4
	OHPA-3P4-2-2	30	700	15	2.8	2	1.5	40	4.7
	OHPA-3P4-2-3	30	700	15	2.8	3	1.9	40	5.3
	OHPA-3P4-2-4	30	700	15	2.8	4	3.5	40	6.2

1600 bar

Pump Stage	Model	Pressure (kg/Cm ²)		Flow / stroke (cc)		Filling Capacity (ltrs.)	Usable Oil (ltrs.)	Handle Effort (kg)	Dry Weight (kg)
		1 st stage	2 nd stage	1 st stage	2 nd stage				
Two	OHPA-3P2-6-1.5	30	1600	15	1.2	1.5	1	40	4
	OHPA-3P2-6-2	30	1600	15	1.2	2	1.5	40	4.7

2800 bar

Pump Stage	Model	Pressure (kg/Cm ²)		Flow / stroke (cc)		Filling Capacity (ltrs.)	Usable Oil (ltrs.)	Handle Effort (kg)	Dry Weight (kg)
		1 st stage	2 nd stage	1 st stage	2 nd stage				
Two	OHPA-3P6-7-1.5	30	2800	15	0.7	1.5	1	40	4
	OHPA-3P6-7-2	30	2800	15	0.7	2	1.5	40	4.7

■ Higher capacity and customized solutions on request. ■ Specifications are subject to change due to continual improvement.

CUSTOMISED SOLUTIONS

